
TRENDS HOMEOWNER LIBRARY

WINTERIZE YOUR HOME

Inside and Out

The Complete Kansas City Homeowner Guide

2026



BY DAMON FOWLER
Trends Kitchen & Bathroom Specialists

Winterize Your Home: Inside and Out

By Damon Fowler
Trends Kitchen & Bathroom Specialists

A practical, inside-and-out guide for Kansas City homeowners • Updated October 2026

The first cold night has a way of revealing what the rest of the year allowed you to overlook. The back door whistles. The upstairs bedroom never quite warms up. Water collects beside the basement wall after a thaw. A garden hose is still connected to the faucet behind the shrubs.

Winterizing your home means finding those weak points while you still have time to make thoughtful repairs. Some tasks take a few minutes. Others need a service appointment, a closer diagnosis, or a planned construction project. Knowing which is which can save you from spending money on the wrong solution.

This guide follows the house from the roof to the foundation, then moves through its plumbing, heating, indoor moisture, and emergency plans. Each chapter answers a question homeowners actually face and includes situations that show how to think through the problem. The examples are illustrative, rather than claims about particular Trends clients.

Use the table of contents to start with your immediate concern, then complete the seasonal walkthrough. You do not need to buy every product mentioned or complete every improvement this year. Your first priorities are a safe home, reliable heat, controlled water, and plumbing that stays protected when temperatures fall.

Kansas City spans multiple municipalities and two states. Permit requirements, utility procedures, and building conditions vary. For installations and specialized repairs, the selected equipment instructions and your local requirements govern. This is homeowner education, with practical boundaries between observation, manageable maintenance, and work that belongs with a qualified professional.

[Read the complete guide and separate chapters online](#)

Cover artwork is illustrative. This PDF reproduces the existing complete guide, including its practical examples, qualifications, and source references.

Contents

- Chapter 1: Where should I start, and what deserves attention first?
- Chapter 2: What makes winter preparation different in the Kansas City area?
- Chapter 3: How do I keep rain and snowmelt away from the foundation?
- Chapter 4: How do I inspect the roof and reduce the risk of ice dams?
- Chapter 5: Which exterior gaps should I seal—and which should stay open?
- Chapter 6: How can I stop window and door drafts without replacing everything?
- Chapter 7: What should I know before adding attic insulation?
- Chapter 8: Why are rooms over garages, basements, and crawl spaces so cold?
- Chapter 9: How do I winterize outdoor faucets, hoses, and irrigation?
- Chapter 10: How do I protect indoor pipes—and respond if one may be frozen?
- Chapter 11: What does a useful furnace or boiler readiness check include?
- Chapter 12: What thermostat setting makes sense, and are heat pumps different?
- Chapter 13: How do I manage winter humidity, condensation, and ventilation?
- Chapter 14: What winter problems should I check in kitchens and bathrooms?
- Chapter 15: How do I check a sump pump and prepare the basement for a thaw?
- Chapter 16: How do I prepare fireplaces, chimneys, alarms, and portable heaters?
- Chapter 17: How do I make decks, porches, walks, and entries ready for ice?
- Chapter 18: What outdoor equipment, vents, and seasonal items should I check?
- Chapter 19: What should I do before and during a winter power outage?
- Chapter 20: How do I prepare the house before winter travel or an extended vacancy?
- Chapter 21: How should I schedule and budget winterization work?
- Chapter 22: What are the winterization questions homeowners ask most often?

Chapter 1: Where should I start, and what deserves attention first?

Start with a notebook, a flashlight, your phone camera, and a walk around the house. Resist the temptation to begin at the home-improvement store. Until you know what is wrong, a cart full of caulk, insulation, and faucet covers is only a collection of possible answers.

Separate an urgent condition from an improvement

An active roof leak, a suspect gas odor, unreliable heat, or water near electrical equipment needs prompt attention. A slightly uncomfortable bedroom may need investigation but rarely deserves the same immediate response. A room you wish were prettier can wait while a wet wall is diagnosed.

Use three priorities. First, identify immediate safety and active water problems. Second, address conditions likely to fail during a freeze, such as an exposed water line or a heating system that repeatedly stops. Third, plan comfort and efficiency improvements. This order keeps a cosmetic project from consuming the money needed for essential work.

Inspect without creating a new hazard

Look at roof surfaces from the ground or through a safely positioned window. Stay out of an attic with unsafe access, unknown loose insulation, exposed wiring, or no secure footing. Do not enter standing water to inspect a pump or panel. Photographs from a safe position can give a specialist useful starting information.

Record the location, symptom, weather conditions, and when the issue appears. “Water at the northeast basement corner after a thaw” is more useful than “basement damp.” The timing can help distinguish precipitation entry from indoor condensation or a plumbing leak.

A practical example

Imagine that you find a cold kitchen floor, a dark patch under the sink, and a loose door sweep. The sweep may be a straightforward maintenance item. The under-sink patch needs a leak check before new shelving is installed. The cold floor might involve air leakage, missing insulation, a plumbing route, or the construction below it. These findings should not all lead to the same purchase.

For each issue, write the next action rather than jumping to a final diagnosis: inspect supply and drain connections, identify the space below the kitchen, photograph the door bottom, or book a heating service. This turns a vague winter to-do list into a manageable set of decisions.

Build a small home reference file

Keep equipment model numbers, service contacts, filter specifications, shutoff locations, and recent repair records together. Include photographs showing the normal appearance of vulnerable areas. A dated photograph of a foundation crack, for example, provides a better comparison than memory alone.

At the end of your walkthrough, choose the few tasks with the greatest consequence if ignored. Book specialist work early, complete accessible maintenance, and give uncertain conditions an assessment before covering them. Winter preparation works best when it is specific to your house.

[Read this chapter online](#)

Chapter 2: What makes winter preparation different in the Kansas City area?

A useful Kansas City winter plan prepares for changing conditions rather than one long stretch of identical weather. A mild afternoon can be followed by a hard freeze. Snow can melt while the ground remains cold, and wind can expose a draft that is barely noticeable on a calm day. Plan for the transitions as well as the coldest forecast.

Follow conditions, not a date on the calendar

“I always disconnect the hoses in November” is less reliable than checking the forecast and finishing before freezing weather. The same applies to exterior sealants, coatings, and winterizing equipment. Their installation or storage instructions may require conditions that disappear before the first snow.

Use the [National Weather Service Kansas City/Pleasant Hill office](#) for local forecasts and alerts. Look beyond the daytime high. Overnight temperatures, precipitation type, wind, and the duration of cold all affect which parts of the property need attention.

The house matters as much as the neighborhood

An older home with several additions can have plumbing routes that make little sense from the finished room. A bathroom above a garage has different exposures from one over a conditioned basement. An earth-contact home may have a limited exterior wall area but still depend heavily on effective drainage and ventilation.

Even adjacent homes can need different solutions. One may have a vented attic with insulation at the ceiling; another may have a conditioned roof assembly. One exterior faucet may have an accessible interior shutoff while another uses a different design. Identify the assembly you have before applying a generic checklist.

Situation: the addition freezes before the rest of the house

Suppose an enclosed former porch now serves as a laundry room. The room has a supply register, but the floor sits above an exposed or poorly enclosed space. Water lines pass near the outside edge. A thermostat in the central hallway may report a comfortable temperature while the laundry plumbing remains at risk.

The useful response is to document that exposure and have the enclosure, insulation, pipe location, and heating arrangement evaluated together. A warmer thermostat setting alone may not deliver heat to the vulnerable cavity. Finishing the floor with a thicker surface material will not establish freeze protection.

Plan for thaw water

A blocked downspout extension or sump discharge may become most obvious after temperatures rise. Walk the property after a safe thaw and note where water travels. Pay particular attention to basement windows, exterior stairwells, low spots, and the paths people use between the driveway and door.

Keep local rules in mind when changing drainage, adding electrical equipment, or altering heating and plumbing. Requirements can differ across Kansas City, Parkville, Liberty, Overland Park, and other metro communities. Ask the relevant municipality and utility rather than assuming the rule from another project applies. Regional experience helps identify likely problems; inspection of the actual home determines the repair.

[Read this chapter online](#)

Chapter 3: How do I keep rain and snowmelt away from the foundation?

Many winter basement problems begin above ground. Water leaves the roof, reaches a blocked gutter or disconnected downspout, and lands beside the foundation. When that happens repeatedly, an interior coating or a dehumidifier may do little to address the source.

Follow one drop from the roof to its destination

Look at each gutter run, downspout, extension, and outlet as a continuous route. A clean gutter is only one part of it. A downspout can be clear at the top and blocked underground. An extension can point away from the house yet discharge into a depression that sends water back.

When weather and footing permit, observe the system during ordinary rain from a sheltered, safe location. Look for gutter overflow, leaks at joints, water running behind the gutter, and discharge that pools. Record where the water actually ends up rather than where the pipe appears to point.

Situation: the basement corner gets wet after every thaw

Imagine a downspout connected to an underground line near that corner. It looks tidy, but the buried outlet has disappeared under soil and leaves. Water may be backing up at a hidden break or spilling at the connection.

Locate and assess the outlet before assuming the foundation needs a major interior treatment. A drainage professional can determine whether the line is blocked, damaged, or poorly routed. A temporary surface arrangement may be appropriate while a permanent repair is planned, but it must discharge to a safe, lawful location without creating an icy walkway or affecting a neighbor.

Inspect the ground beside the house

Look for settled soil, depressed planting beds, and hard surfaces that direct water toward the foundation. Mulch can conceal a low area without correcting it. Keep siding clearances and drainage details intact; do not pile soil against wood framing or bury openings while trying to change the grade.

Major grading changes deserve a plan. They can affect doors, window wells, retaining walls, utility routes, and adjoining properties. Ask how surface water will be collected and discharged, and what happens when an inlet is blocked or covered in snow.

Give window wells and stairwells their own check

Remove accessible leaves and debris without entering an unsafe opening. Check that any cover is sound, appropriate to the installation, and does not interfere with required emergency escape. A cover does not substitute for a functioning drainage system. Look for staining at the window or stairwell threshold that indicates recurring overflow.

Keep a simple record of which drains connect where. If you cannot identify the destination, mark it as unknown. That is useful information for the person evaluating it.

What good maintenance can and cannot do

Maintaining roof runoff routes is worthwhile even when a basement also has a sump system or interior drainage. Those systems serve different parts of the water-management problem. Persistent seepage, moving walls, or changes in cracks still call for professional assessment. Begin with visible water routes, then investigate what remains after those are functioning.

[Read this chapter online](#)

Chapter 4: How do I inspect the roof and reduce the risk of ice dams?

Roof preparation starts before anything freezes. From the ground, look for displaced shingles, damaged flashing, loose gutters, deteriorated fascia, and stains beneath roof edges. Indoors, note ceiling discoloration and any history of leakage around chimneys, skylights, or roof intersections.

Understand the ice-dam mechanism

An ice dam can form when snow melts on a warmer upper roof and the water refreezes at a colder eave. The resulting ice can hold back water, allowing leakage into the roof assembly. Clearing leaves from gutters helps drainage, but it does not by itself correct heat escaping into the roof.

For a conventional vented attic, reducing unwanted heat flow through air sealing and adequate insulation is central to prevention, with ventilation part of the assembly. [Building Science Corporation's explanation of ice dams](#) describes why the ceiling-to-roof details matter. The correct solution depends on the roof design; an unvented roof needs its own assessment.

Situation: one section melts sooner than the rest

Suppose snow repeatedly disappears above a bathroom while remaining elsewhere. That pattern can be a clue to heat reaching the roof, but it is not proof of one defect. Sun exposure, roof orientation, ducts, air leaks, and insulation differences can all influence it.

Photograph the pattern safely and share it with an energy or roofing professional. Ask about the attic hatch, bath-fan duct, recessed fixtures, and other

penetrations in that area. Do not assume that adding more roof vents will solve a ceiling air leak.

Keep inspection separate from roof work

Do not climb onto a snowy or icy roof to clear an obstruction. Avoid chipping ice with tools, pouring hot water along the eaves, or using open flame. These actions can damage the roofing and put you beneath falling ice or on a hazardous surface.

If an active ice problem needs removal, use a qualified contractor with a method suited to the roof. A roof rake is not appropriate for every slope, material, or location; overhead wires, falling snow, and limited footing can make even ground-based removal unsafe. Get guidance specific to the house.

Fix the leak, then fix why it happened

A roof membrane or flashing detail may limit water entry, but it is not a complete substitute for addressing excess heat flow. Likewise, more insulation does not repair missing flashing. A durable plan may involve both the roofing contractor and an insulation or building-performance specialist.

After a leak, inspect affected interior materials and document what became wet. Do not repaint a stain while moisture is still present. Confirm the source is corrected and the assembly has dried appropriately before finishes are restored. This is especially important where new bathroom or kitchen finishes conceal the roof or wall cavity below.

[Read this chapter online](#)

Chapter 5: Which exterior gaps should I seal—and which should stay open?

A tube of sealant is useful only when it goes in the right joint. Exterior walls are designed to manage water, and some openings allow that water to drain. Covering every visible gap can trap moisture rather than keep it out.

Identify the joint before choosing the product

Inspect accessible window and door trim, utility penetrations, siding transitions, and previously sealed joints. Look for sealant that has pulled away, split, become brittle, or lost adhesion. Note whether the material beneath it is firm and dry or soft and stained.

Check the window or siding manufacturer's details where available. Weep openings, drainage slots, and required ventilation spaces need to remain functional. A gap at a designed drainage point and a failed perimeter joint may look similar to someone unfamiliar with the assembly.

Situation: caulk keeps cracking at the same window

Imagine a joint that has been covered with new caulk every fall. The surrounding trim is soft at the bottom, and the replacement material separates again by spring. The issue may involve wet or deteriorated substrate, joint movement, poor preparation, or an unsuitable sealant.

Adding another bead over the old material does not investigate those causes. Have damaged trim and the water-entry path evaluated. The repair may require removing failed material, correcting flashing or drainage, replacing deteriorated components, and then sealing the intended joint.

Prepare the surface rather than decorating the defect

For a sound joint suitable for homeowner maintenance, remove failed sealant as directed without damaging adjacent surfaces. Clean and dry the joint, observe application-temperature and weather restrictions, and use a product compatible with both materials. Some joints need backer material or a specific geometry for the sealant to move correctly.

Read the label for paintability, adhesion, cure conditions, and exposure. A bathroom sealant is not automatically the right exterior product. Paint can fail over a sealant that is not designed to accept it, and a product applied to a wet or freezing surface may not perform as expected.

Penetrations deserve more than a ring of foam

Where pipes, cables, vents, or conduits pass through the wall, assess both weather protection and the opening's purpose. Combustion vents, hot components, electrical equipment, and fire-resistance requirements need appropriate materials and clearances. General-purpose expanding foam is not a universal repair.

If the opening serves an appliance or contains damaged wiring, leave its repair to the appropriate professional. Do not seal a required air inlet because

it feels drafty.

Check what is touching the wall

Vegetation, stored materials, and piled mulch can hide deterioration and hold moisture against finishes. Improve access for inspection and keep required clearances intact. Photograph suspect areas before cleaning them so the original pattern remains documented.

The goal is a wall that sheds and drains water as designed while limiting unintended air leakage. When the design is unclear, identifying the assembly is the next step - not applying more product.

[Read this chapter online](#)

Chapter 6: How can I stop window and door drafts without replacing everything?

A drafty opening does not automatically require a new window or door. The leak may be at a worn weatherstrip, an unlatched sash, a door bottom, or the connection between the frame and the wall. The best repair starts by locating it.

Inspect on a cool, windy day

Close and latch the window normally, then check accessible edges with your hand. Look for damaged weatherstripping, loose stops, a sash that does not seat, or a latch that pulls unevenly. With doors, inspect the sweep, threshold, corner seals, and alignment.

A strip of paper gently held between the closed door and its weatherstrip can help compare compression along the perimeter. It is a simple observation, not a precision air-leakage test. Do not force a latch or make adjustments that compromise safe operation.

Situation: daylight shows beneath the back door

Suppose the door closes well at the handle but leaves a visible gap at one bottom corner. Replacing the sweep might help, but an uneven threshold, sagging hinge, or distorted door can be involved. Inspect alignment before installing a thicker seal.

An overly tight sweep can make the door difficult to latch and wear prematurely. A door that must be

slammed is not a successful weatherization result. Use compatible replacement components and follow the door manufacturer's adjustment guidance.

Know where condensation is located

Moisture on the room-side glass is different from fog trapped between insulated panes. Interior condensation can involve indoor humidity and cold surface temperatures. Moisture between panes may indicate failure of the insulated glass unit. Caulking the trim will not restore that sealed unit.

Check the surrounding frame and wall for staining or deterioration. Water arriving from outside needs a different response from room moisture condensing on glass. Document when it appears and whether it follows rain, cold weather, or household activities.

Use temporary improvements thoughtfully

A suitable interior window-film kit can reduce drafts at an appropriate opening, but adhesion, finish compatibility, and removal instructions matter. Keep emergency escape windows usable and accessible. Do not seal shut an opening that must operate for safety or needed ventilation.

Curtains can improve comfort near cold glass, but do not cover heat registers or let fabric contact heaters. Heavy coverings may also reduce warm-air circulation at the window, so check behind them for condensation instead of assuming the hidden surface stays dry.

When replacement makes sense

Persistent frame deterioration, poor operation, unsuitable glazing, or broader installation problems may justify replacement. Ask the contractor to distinguish the condition of the unit from the condition of the wall opening. A new window installed into an unresolved water problem can inherit the same trouble.

For several uncomfortable rooms, an energy assessment can establish whether windows are the largest issue or simply the most noticeable cold surface. That comparison helps you decide between targeted repair, air sealing, insulation work, and replacement without guessing.

[Read this chapter online](#)

Chapter 7: What should I know before adding attic insulation?

Insulation resists heat flow, but it does not automatically stop air moving through gaps. An attic can contain a generous amount of insulation and still lose warm indoor air through unsealed ceiling penetrations. That is why air sealing and insulation should be considered together.

Determine where the thermal boundary belongs

In a conventional vented attic, the insulated and air-sealed boundary is usually at the ceiling below. Other roof assemblies are designed differently. Before adding material, confirm whether the attic is intended to be outside the conditioned space or part of it.

Ask an insulation or energy professional to evaluate existing coverage, material condition, air leakage, ventilation provisions, and moisture evidence. Recommend an insulation level for the actual assembly and climate rather than choosing a depth from an unrelated photograph. Different materials provide different performance per inch.

Situation: the attic hatch is the missing piece

A hallway feels drafty despite insulated ceilings. The attic access panel is a thin, unsealed cover. In that case, improving the hatch's insulation and perimeter seal may address a concentrated weakness that adding loose insulation elsewhere would miss.

The closure still needs to operate safely and remain accessible. Pull-down stairs require a compatible approach that does not interfere with hinges or create a hazard for the next person entering the attic. Treat access details as part of the system.

Deal with moisture and hazards first

Do not cover wet insulation, roof leakage, mold-like growth, damaged wiring, or suspect older materials with a new layer. Have unknown vermiculite or other potentially hazardous material assessed before disturbance. Moving it to take a closer look can create unnecessary exposure.

Recessed fixtures, chimneys, flues, and heat-producing equipment have specific clearance requirements. A fixture that looks ordinary from below

may not be suitable for insulation contact. Use approved details and qualified help where required rather than packing material around every obstruction.

Preserve the intended ventilation path

In a vented attic, insulation can obstruct soffit intake unless appropriate baffles and details are maintained. Blocking vents to keep the attic warmer can create a different set of problems. Conversely, adding ventilation alone does not fix uncontrolled indoor air leakage into the space.

ENERGY STAR's [attic air-sealing guidance](#) explains why the work needs to be coordinated. Use that as a planning reference, then follow the requirements of the actual roof assembly and selected materials.

Ask for documentation

Before and after photographs should show the difficult details, not only a wide shot of a fresh white blanket. Record air-sealing locations, treatment of access panels, ventilation paths, and the installed insulation specification. Keep equipment and junctions accessible as required.

This work may never appear in a finished-room photograph, yet it can affect comfort, moisture behavior, and future maintenance. It deserves the same deliberate planning as visible remodeling.

[Read this chapter online](#)

Chapter 8: Why are rooms over garages, basements, and crawl spaces so cold?

A cold floor is a clue about the construction around it. A bedroom above a garage, a bathroom over a crawl space, and a finished basement can all feel uncomfortable for different reasons. A thicker rug may improve the sensation underfoot without correcting the underlying exposure.

Locate the cold boundary

Identify what lies on the other side of the floor or wall: outdoors, an unheated garage, a vented crawl space, soil, or another conditioned room. Note whether the discomfort is strongest on windy days, near one edge, or throughout the space.

Check visible openings and accessible insulation without dismantling fire-rated assemblies or disturbing unknown materials. Garage-to-house separations also serve fire and air-quality functions. Repairs to those boundaries need to maintain the required protection, not simply fill cavities.

Situation: the bathroom above the garage stays cold

Imagine that the bathroom has a heat register, yet the vanity floor and exterior corner remain chilly. Possible contributors include incomplete insulation, air movement through the floor cavity, duct performance, and pipe placement. The hall thermostat cannot reveal the temperature inside that cavity.

Have the enclosure, air barrier, insulation, HVAC delivery, and water-line route evaluated together. Adding electric floor warming may improve comfort but does not by itself protect a concealed pipe near an exterior air leak. Correct the assembly before choosing the finish upgrade.

Keep moisture out of the insulation decision

A basement wall with recurring seepage needs water management before it is covered. Insulating and finishing a wet wall can conceal deterioration and complicate later repairs. Ask where water is entering, how it will drain, and how the wall will dry after the proposed construction.

Crawl spaces also vary. A vented crawl space and a properly designed conditioned crawl space are different systems. Do not close vents, add a heater, or line surfaces with plastic at random. Changes can affect moisture, combustion equipment, pests, and indoor air quality.

Watch for mechanical routes

Ducts, drains, and water lines may pass through unconditioned zones even when the finished room looks completely interior. A closet behind a bathroom or a dropped soffit can hide a vulnerable route. Existing drawings and photographs from previous work are useful, but verify them against what is actually there.

If a pipe has frozen before, that history deserves specific attention. The fact that it survived last winter is not evidence that it is adequately protected for a longer or windier cold spell.

Use remodeling access wisely

When a kitchen, bathroom, or basement project opens the relevant area, address these hidden conditions before installing new surfaces. Photograph the repaired boundary and pipe routes. Keep a record of what was changed so future work does not undo it.

The most useful comfort improvement may be a coordinated repair behind the wall rather than another visible layer. A room that looks finished should also be supported by an enclosure that performs.

[Read this chapter online](#)

Chapter 9: How do I winterize outdoor faucets, hoses, and irrigation?

Walk the entire exterior and count the water connections. Include the faucet behind the shrubs, the one inside the garage, hose splitters, timers, outdoor shower connections, irrigation equipment, and any water supply to an outdoor kitchen. The connection you forget is often the one most exposed.

Disconnect the attachments first

Remove hoses, splitters, timers, and other attachments from hose-threaded faucets before freezing conditions. Drain and store portable components according to their instructions. A hose left connected can prevent a frost-resistant wall faucet from draining as intended.

The faucet's design matters. Some exterior lines have a separate interior isolation valve and a specific draining procedure. Others use different arrangements. Locate the model or have a plumber identify it; do not force unfamiliar valves or assume that every outdoor faucet should be treated identically.

Situation: the frost-free faucet froze anyway

A homeowner leaves a hose and shutoff nozzle attached because the faucet is labeled frost-free. Trapped water remains in the barrel, and damage becomes apparent when the faucet is used later. Another installation may have an incorrect pitch or a valve seat exposed to an inadequately heated space.

PRIER's **product guidance** identifies attached hoses and improper drainage pitch among common causes of freeze damage. A foam cover does not correct either defect. If an exterior faucet has a history of freezing or leaks inside when operated, stop using it and arrange an assessment.

Use covers as a supplement

A compatible insulated cover can reduce exposure at some installations, but it does not generate heat or make a defective arrangement safe. Fit it as directed after completing the faucet's actual winterization procedure. Check that it does not conceal an ongoing leak.

Keep a photograph of the matching interior shutoff if one exists. Label it accurately so someone does not close the wrong branch during an emergency. If the valve is seized, corroded, or leaking, have it serviced instead of applying greater force.

Irrigation needs its own procedure

Sprinkler systems can contain backflow devices, valves, low points, and controls that need specific treatment. Turning the controller off is not the same as removing water from vulnerable components. Compressed-air winterization requires suitable equipment and limits; excessive pressure or an improvised connection can cause injury or damage.

Use a qualified irrigation service when the procedure is not clearly within your experience. Ask what was isolated, drained, or serviced and how spring reactivation should be handled. Protect backflow equipment according to its manufacturer and local requirements.

Check outdoor kitchens and water features

A sink supply, refrigerator water line, fountain pump, or decorative basin may need draining, removal, or a different storage method. Follow each component's instructions. Do not add automotive antifreeze to household plumbing or water features as a general shortcut.

Finish by verifying that portable water containers and hoses will not trap water where expansion can damage them. Put seasonal parts together and note any spring inspection needed. A complete inventory turns outdoor winterization from a memory test into a repeatable routine.

[Read this chapter online](#)

Chapter 10: How do I protect indoor pipes—and respond if one may be frozen?

Plumbing can be at risk inside the building footprint. Water lines in exterior walls, garages, crawl spaces, poorly enclosed additions, and cabinets isolated from room heat deserve attention. The important temperature is the one around the pipe, which may differ substantially from the thermostat reading.

Find the exposure before wrapping the pipe

Trace accessible lines and note where they enter cold spaces. Look for nearby exterior air leaks, missing enclosure materials, or an area that has frozen previously. A plumber or building-performance specialist may need to investigate concealed routes.

Insulation slows heat loss; it does not supply heat indefinitely. A pipe in a space that remains below freezing can eventually freeze despite insulation. A lasting correction may involve relocating it, repairing the enclosure, or designing suitable protection for that installation.

Situation: only the kitchen faucet stops flowing

After a severe cold night, other fixtures work but the kitchen sink has little or no flow. That pattern suggests a local issue, potentially freezing, but it does not prove it. A blocked aerator or valve problem can also affect flow.

Note whether hot, cold, or both are affected and whether nearby surfaces feel unusually cold. Do not dismantle concealed plumbing or apply heat into a wall cavity to test a theory. If freezing is suspected, contact a plumber, especially if the affected line is inaccessible or the condition is recurring.

Prepare before severe weather

The **American Red Cross** recommends maintaining heat, disconnecting outdoor hoses, and allowing warm room air to reach vulnerable sink plumbing. If you open cabinet doors, first move chemicals and other hazards away from children and pets. For a vulnerable supply during severe cold, a small trickle can help, but it is not a replacement for correcting exposure.

Know where the main water shutoff is and how to reach it safely. Never use a torch or open flame to thaw a pipe. If a line is damaged, inaccessible, or cannot be safely located, get qualified help. Water can begin escaping as a frozen section thaws.

Heat cable is a specified system, not a generic wrap

Use only a listed product suitable for the pipe material, location, electrical supply, and insulation arrangement. Follow the manufacturer's instructions for cable routing, controls, connection, and inspection. Some products have different rules for overlap or coverage. Do not improvise with roof-deicing cable or use a damaged product.

A qualified installer can determine whether heat tracing is appropriate or whether the pipe location itself needs correction. Leave any electrical changes to the proper trade.

Make the later repair part of the response

Once service is restored, document the affected route and what conditions caused concern. A freeze that caused no visible leak still reveals vulnerability. Ask whether the pipe, connections, surrounding material, and enclosure need further inspection.

During a future remodel, make this a design requirement: water lines need a protected route and practical access. Beautiful cabinets should not conceal a recurring winter emergency.

[Read this chapter online](#)

Chapter 11: What does a useful furnace or boiler readiness check include?

A system that produced heat last spring is not automatically ready for the first demanding winter night. Arrange routine service according to the equipment guidance and service history, especially when there have been reliability problems. The appointment is also a chance to understand your system rather than simply collect a service sticker.

Tell the technician what you have observed

Write down unusual noises, repeated shutdowns, uneven rooms, error messages, and changes in operation. Include when they occur: only during strong wind, after a long setback, or during the coldest nights. A specific symptom can help the technician reproduce and diagnose the problem.

Ask what was inspected and what remains uncertain. Combustion safety, venting, electrical components, controls, drainage where applicable, and airflow deserve attention appropriate to the equipment. This is specialist work; do not remove safety devices or adjust combustion components yourself.

Situation: the furnace runs, stops, then starts again repeatedly

Short operating cycles can have several causes, including airflow restrictions, controls, sizing, or safety limits responding to a fault. Repeatedly resetting the unit without diagnosis can hide a continuing problem.

Record the behavior and contact an HVAC professional. If there is a gas odor, suspected combustion problem, or a carbon monoxide alarm, move to safety and contact emergency services or the utility as appropriate. Do not remain inside troubleshooting an alarm condition.

Match the filter to the equipment

Record the filter size, type, orientation, and the manufacturer's service instructions. Check its condition regularly, with frequency informed by the equipment, household conditions, pets, and nearby construction. A fixed "every three months" rule does not suit every filter or home.

A more restrictive filter is not automatically an upgrade. The system must be able to handle its resistance, and the filter must fit correctly. Ask the technician what specification is appropriate. Do not stack filters or add extra material in an attempt to improve filtration.

Inspect the accessible air path

Keep supply registers and return grilles clear of furniture, rugs, and stored items. Note rooms that remain uncomfortable and whether closed doors change the result. Avoid randomly closing many registers to force heat elsewhere; ask for distribution and pressure issues to be evaluated.

Keep the equipment area accessible and observe required clearances. Stored paint, boxes, and seasonal decorations should not crowd appliances or their service access. Do not block openings that provide combustion air.

Boilers and hydronic systems need different attention

A boiler is not a furnace with a different name. Pumps, water pressure, controls, expansion components, radiators, and freeze protection introduce different maintenance questions. Follow the service requirements for the actual system and ask before changing valves or shutting off its water supply.

Make a plan for a heating failure before one occurs. Keep the service contact and model information accessible, identify a safe place to stay if the house cools, and account for water-dependent systems. Reliable heat is essential protection for both people and the building.

[Read this chapter online](#)

Chapter 12: What thermostat setting makes sense, and are heat pumps different?

There is no single winter thermostat number that suits every household and protects every pipe. Comfort needs, heating equipment, insulation, room layout, and vulnerable spaces all matter. Use a starting point, observe the house, and adjust with the system in mind.

Choose a workable occupied temperature

The Department of Energy's consumer guidance suggests starting around **68-70°F and adjusting as needed**. That is a comfort and efficiency starting point, not a requirement or a promise of a particular bill. Household members with greater sensitivity to cold may need a different setting.

Compare room temperatures during normal use rather than relying on one hallway display. An inexpensive thermometer can help establish whether the uncomfortable room is actually colder or feels cold because of nearby surfaces or moving air.

Situation: you keep raising the thermostat for one bedroom

The living room overheats while a bedroom above the garage remains uncomfortable. Raising the setpoint affects the entire system but may not correct that room's enclosure or air distribution.

Document the temperature difference, check for blocked registers, and arrange an evaluation of the room and system. The problem may require air sealing, insulation, duct repair, balancing, or another change. A smart thermostat with a remote sensor can alter control behavior, but it cannot repair a deficient floor cavity.

Understand setbacks before programming them

Lowering the temperature during sleep or absence can reduce heat demand in suitable circumstances. However, large setbacks are not appropriate for every system or household. Recovery time, weather, plumbing exposure, and control strategy matter.

Heat pumps may use supplemental heat during recovery, depending on the equipment and controls. Ask your installer whether a modest schedule, steady setting, or a compatible adaptive control is the best approach. Do not assume a schedule written for a gas furnace is ideal for your heat pump.

Likewise, do not use an emergency-heat setting as a general response to colder weather without understanding its purpose. Follow the equipment guidance and have unusual operation assessed.

Why 55°F is not a pipe-protection guarantee

The commonly cited minimum for an unattended heated house cannot describe every hidden space. A pipe in an exterior wall or unheated addition may be much colder than the room containing the thermostat. Longer cold spells, wind, and a power failure can change the risk.

Before traveling, have vulnerable routes evaluated and make an inspection plan. Consider your insurer's requirements and any water-dependent equipment. A thermostat setting is one part of that plan, not the entire plan.

Make smart controls understandable

Check schedules, time settings, batteries where applicable, and behavior after a power interruption. Know how to cancel a temporary hold and how household members can change the temperature without an app. Keep access credentials and setup information under homeowner control.

If adding a connected thermostat, verify compatibility with the heating system and wiring. Correct installation and commissioning matter more than the display. The best control supports the equipment and the people living with it.

[Read this chapter online](#)

Chapter 13: How do I manage winter humidity, condensation, and ventilation?

Dry skin and fogged windows can occur in the same house. Indoor moisture varies by room and activity, while cold surfaces determine where condensation appears. Adding a humidifier without checking those conditions can improve one complaint and worsen another.

Measure before adjusting

Use a hygrometer to track relative humidity in representative occupied rooms. Note readings alongside outdoor conditions and visible condensation. A single reading beside a shower or directly above a humidifier does not represent the whole house.

The EPA recommends keeping indoor humidity below 60 percent and, when possible, ideally between 30 and 50 percent for moisture control. In severe cold, some windows or assemblies may require lower humidity to avoid condensation. Treat the [EPA guidance](#) as a general framework, then respond to the building and its occupants.

Situation: water runs down the bedroom windows each morning

Several conditions may contribute: indoor moisture, cold glazing, limited airflow behind heavy curtains, or a building defect. First establish whether the moisture is on the room side, between panes, or arriving around the frame.

Track overnight conditions, inspect nearby finishes, and review moisture sources. Reduce excess moisture and have persistent or localized problems assessed. Replacing a window may help in some circumstances, but it should follow diagnosis rather than serve as the default answer to every wet surface.

Remove moisture near its source

Use bathroom exhaust during bathing and continue it as appropriate for the room and control arrangement. Verify that the exhaust path reaches outdoors. Kitchen and laundry ventilation also affect moisture; equipment needs proper installation and a clear route.

A noisy fan that barely moves air deserves inspection of the entire path, including the duct and termination. A timer or humidity control can improve consistency, but it cannot compensate for a blocked or disconnected duct. ENERGY STAR highlights [direct outdoor bathroom exhaust](#) as an indoor-air-quality feature in certified homes.

Do not solve drafts by disabling ventilation

Fresh-air systems, combustion-air openings, and exhaust provisions have different purposes. Sealing an opening because cold air is noticeable can interfere with safe operation or moisture control. Ask a professional to identify it and evaluate the complaint.

A tighter house may need ventilation and combustion-safety considerations alongside air sealing. The objective is controlled air exchange, not a house with every opening plugged.

Humidifiers need maintenance, too

Follow cleaning, water-quality, and service guidance for the selected unit. Check for leaks and keep output appropriate to the building conditions. If windows, corners, or concealed areas show recurring moisture, investigate rather than simply wiping it away every morning.

Visible growth, persistent mustiness, and water-damaged materials call for attention to the moisture source and an appropriate cleanup or repair plan. Do not cover a damp area with paint or new cabinetry and consider the issue resolved.

[Read this chapter online](#)

Chapter 14: What winter problems should I check in kitchens and bathrooms?

Kitchens and bathrooms concentrate water, plumbing penetrations, ventilation, and finished surfaces in a small area. That makes them useful places to look for winter weaknesses - and poor places to hide a developing problem behind a quick cosmetic repair.

Empty the sink base for a real inspection

Remove stored items and inspect the cabinet floor, back, supply connections, drain, and accessible shutoffs. Look for swelling, stains, corrosion, moisture, or a persistent odor. Dry the area and observe accessible connections during normal use without touching electrical equipment or opening concealed plumbing.

Store household products so they do not press against valves, disposals, or pipe connections. Keep a small leak from remaining hidden under a crowded collection of bottles. If a valve appears deteriorated, arrange service rather than forcing it as an experiment.

Situation: the sink cabinet smells damp only in winter

Possible causes include a small plumbing leak, condensation, outdoor air reaching a cold cavity, or water entering from elsewhere. A smell does not establish the source. Note whether the cabinet is on an exterior wall and whether nearby plumbing has ever frozen.

Have the moisture and enclosure checked before adding an interior lining or replacing only the cabinet bottom. A new surface can conceal the evidence while leaving the original cause active.

Inspect the toilet and shower perimeter

Look for changes around the toilet base, soft flooring, stained trim, or movement. A rocking toilet needs evaluation; adding caulk around a deteriorating base does not repair the connection below. Do not tighten fixtures aggressively in an attempt to stop movement.

In showers, inspect for recurring dampness outside the enclosure, loose tile, failed sealant, or water that collects where it should drain. Surface grout and caulk are only parts of the installation. A failing concealed water-management detail cannot be

repaired by applying sealer to the face of the tile.

Cold floors and poor ventilation deserve separate answers

A tile floor may feel cold because of the material and its surroundings even when room air is comfortable. Floor warming can improve comfort, but first assess insulation, drafts, and any freeze exposure below. It is an added system, not a substitute for correcting a deficient enclosure.

Similarly, a fresh coat of bathroom paint will not correct a fan that exhausts into the attic. Identify the moisture route before selecting the finish repair. Remodeling is the right time to coordinate these hidden conditions because access will later become expensive.

Put practical improvements on the project list

Record shutoff access, storage conflicts, inadequate task lighting, and awkward maintenance points. These observations can shape a kitchen or bathroom refresh even when the layout stays the same. A removable access panel, properly planned ventilation route, or better cabinet organization may offer lasting value.

At Trends, the finished room and the construction behind it belong in the same discussion. Winter inspection provides useful evidence about what that future project should solve.

[Read this chapter online](#)

Chapter 15: How do I check a sump pump and prepare the basement for a thaw?

A sump pump can sit quietly through cold weather and become essential when rain or melting snow increases groundwater. The pump is only one part of the system: the basin, controls, power, check valve, discharge route, and backup arrangement all influence performance.

Identify the equipment before testing

Find the model information and its installation or maintenance instructions. A sump pump is different from a sewage ejector or another covered pumping system. Do not open an unfamiliar sealed basin or disturb a cover that serves a radon, sanitary, or safety function.

Check accessible cords, connections, and the surrounding area visually. If water is near electrical equipment, stay clear and get qualified help. Never reach into a powered basin or handle the pump while it can start.

Test according to the actual system

Many sump systems can be tested by adding clean water gradually until normal automatic operation occurs, but the procedure and access vary. Follow the manufacturer's directions or have a service professional demonstrate the test. A universal instruction to dump five gallons into every pit ignores those differences.

Observe whether the pump starts, lowers the water, stops appropriately, and sends water to the intended outlet. Do not let it run dry or keep adding water when the level is approaching an unsafe height. [Zoeller's product-support resources](#) can help locate information for its equipment; use your own manufacturer's guidance for other systems.

Situation: the pump runs but the level barely falls

Possible causes include a restriction, a frozen discharge, a valve problem, equipment damage, or incoming water that exceeds capacity. The sound of a running motor does not prove that water is leaving the property.

Stop the test and arrange service rather than continuing to run the unit against a suspected blockage. Do not disconnect piping or electrical components while the system is operating. Document the water level and any visible discharge behavior from a safe location.

Follow the discharge outside

Locate the outlet and check for leaves, ice, crushed extensions, or a route that returns water toward the house. Discharge must comply with local rules and avoid creating hazardous ice on walks or neighboring property.

If a temporary hose or extension is used, ask how its installation addresses freezing and maintenance. Do not remove an essential part of the system or create a new outlet without understanding where the water will go.

Plan for loss of power

A battery backup, water-powered backup where suitable, or another designed arrangement can improve resilience, but each has limitations and maintenance needs. Battery condition, controls, water supply, and pump capacity all matter. A high-water alarm can warn you, yet it cannot move water.

Test and maintain the backup as its manufacturer requires. Know who responds when you are away, and keep vulnerable stored items above areas with a history of water entry. After a thaw, inspect the basement even if you never heard an alarm.

[Read this chapter online](#)

Chapter 16: How do I prepare fireplaces, chimneys, alarms, and portable heaters?

Backup warmth is useful only when it is safe. A fireplace that has not been used for years, a portable heater beside bedding, or an ignored carbon monoxide alarm can turn cold-weather improvisation into a serious emergency. Make the safety decisions before the house is cold.

Have fuel-burning equipment assessed

Arrange inspection and service appropriate to the fireplace, chimney, stove, or heating appliance. Tell the professional about smoke entering the room, unusual odors, damaged components, water staining, or poor operation. Do not use an appliance with a known defect while waiting for a convenient repair date.

Different fireplace and vent designs have different operating instructions. Understand damper use, fuel requirements, glass doors, screens, and clearances for the actual unit. Decorative logs and accessories are not interchangeable simply because they fit in the opening.

Situation: the room needs warmth, but the fireplace is unfamiliar

Suppose you bought the house in summer and have never operated the gas fireplace. The safe preparation is to identify it, obtain instructions, and arrange assessment if its condition or service history is uncertain. Turning unfamiliar controls during a power outage is a poor time to learn what they do.

Know whether the unit can operate without utility power and which features depend on electricity. Do not assume every gas appliance will provide usable heat during an outage.

Check alarms and escape routes

Test smoke and carbon monoxide alarms according to their instructions. Check replacement dates, batteries where applicable, and whether the household recognizes the signals. Confirm placement with manufacturer guidance and local requirements. An alarm beyond its service life is not restored by a new battery.

Keep exits usable and discuss how people will leave if a fire or CO alarm occurs. If a carbon monoxide alarm sounds or exposure is suspected, move everyone to fresh air and call emergency services. Do not stay inside searching for the source or assume that opening a window makes it safe to remain.

Use portable electric heaters within strict limits

CPSC advises plugging portable electric heaters directly into a wall outlet, keeping them at least three feet from combustible items, and avoiding unattended operation. Keep cords out from under rugs. Follow the product's instructions, and stop using equipment with damage or signs of overheating. See [CPSC's winter heating guidance](#).

Do not treat a portable heater as a permanent correction for a freezing pipe in an inaccessible cavity. Solve the building exposure with an appropriate design. Never use an oven, grill, or outdoor combustion heater to warm the house.

Leave room for the equipment to work

Keep stored belongings, holiday décor, and furniture away from required clearances and service access. Inspect accessible exterior appliance vents after snow from a safe position. If obstruction, damage, or icing affects operation, contact the service professional.

Warmth, alarms, ventilation, and a clear escape route work together. None should be sacrificed to make the room more comfortable for one cold night.

[Read this chapter online](#)

Chapter 17: How do I make decks, porches, walks, and entries ready for ice?

Winter makes small access problems harder to manage. A loose handrail becomes more consequential when a step is slick. A curled mat becomes difficult to see under a dusting of snow. Prepare the routes people actually use before the first storm.

Walk the route as a guest would

Start at the driveway or sidewalk after dark. Carry a bag, open the gate, approach the steps, and operate the door. Look for uneven surfaces, loose boards, poor drainage, abrupt level changes, and insufficient light. Keep the route practical for household members with limited mobility.

Inspect railings without leaning your weight against a suspect assembly. Movement, corrosion, deterioration, or loose connections needs a repair assessment. Screwing a loose rail into damaged material does not establish a sound attachment.

Situation: the same step freezes after every thaw

Imagine a downspout extension discharging near the front walk. During the day, snow melts and water crosses the path; overnight it refreezes. Repeated applications of deicer manage the symptom while the route remains unchanged.

Correct the drainage source with an appropriate, lawful discharge plan. Also check dripping gutters, porch roof edges, and depressions that collect meltwater. The cause may sit several feet away from the ice patch.

Choose traction measures for the surface

Use snow-removal tools and ice-control products compatible with the concrete, masonry, stone, decking, and nearby vegetation. Read surface and product instructions, especially for newer concrete and specialty finishes. More chemical is not automatically more effective.

Store products where they stay dry and accessible without crossing the very area you need to treat. Choose mats that lie flat, remain secure, and do not hold water against a vulnerable surface. Inspect them during the season rather than leaving them in place until spring.

Check lighting from the walking position

A bright porch bulb can create glare while leaving lower steps dark. Aim for visible edges and a readable route, not simply maximum brightness. Test timers, sensors, and manual controls before relying on them.

Outdoor fixtures and wiring must be appropriate to their exposure. Have a qualified electrician address missing, damaged, or unsuitable equipment. Do not run a permanent lighting solution from an extension cord across a walkway.

Protect outdoor furnishings and structures

Clean and store cushions as directed, secure loose furnishings, and maintain drainage openings. Covers should suit the material and allow the protection and ventilation the manufacturer requires. Trapping moisture under an improvised cover can create its own problem.

For decks and porches, note soft areas, deterioration at posts, and changes where structures meet the house. These are construction issues worth evaluating before adding heavier furniture, a heater, or another feature.

A winter-ready entry should be easy to navigate, maintain, and illuminate. If it needs constant temporary fixes, use that pattern to guide a permanent improvement rather than repeating the same scramble every storm.

[Read this chapter online](#)

Chapter 18: What outdoor equipment, vents, and seasonal items should I check?

The house is connected to equipment and openings that are easy to overlook: dryer outlets, furnace intake and exhaust terminations, air-conditioning or heat-pump units, garage doors, pumps, and outdoor appliances. Winter preparation means identifying them and preserving their intended operation.

Know which outdoor unit runs in winter

An outdoor air-conditioning condenser and an outdoor heat-pump unit may look similar, but their winter roles differ. A heat pump needs outdoor airflow while heating. Do not wrap or cover operating equipment as though it were stored furniture.

Follow the manufacturer's guidance for clearance, snow exposure, and maintenance. Keep leaves and stored objects away without damaging fins, wiring, or piping. Ask the service technician how to recognize normal defrost behavior and when an ice condition calls for service.

Situation: snow storage blocks the mechanical corner

A convenient place to pile shoveled snow may also contain a heat pump, appliance vents, or a basement window. The pile can obstruct airflow or drain toward the house when it melts.

Choose snow-storage areas before a storm. Identify vents and equipment on a simple property sketch, and share it with anyone handling snow removal. Leave access for service and avoid blocking emergency escape openings.

Inspect dryer and other exhaust outlets

From a safe location, look for obvious blockage, damaged covers, or accumulated debris. Do not add screens, insulation, or coverings that conflict with the outlet's design. Dryer vent inspection and cleaning should follow the appliance and duct requirements; a persistent drying problem deserves assessment.

Trace unfamiliar wall openings before sealing them. A cold draft near an inlet does not tell you whether it is unnecessary. Combustion air, mechanical ventilation, and drainage openings serve different purposes.

Prepare seasonal tools using their manuals

Check snow-removal equipment before you need it. Fuel, battery, lubrication, storage, and starting procedures vary. Use approved containers and storage locations for fuels, and keep them away from ignition sources. Do not assume that one additive or charging routine suits every tool.

For powered snow equipment, understand shutdown and clearing procedures. Never put your hand into a chute or mechanism to clear a blockage. Use the manufacturer's prescribed tool and method after disabling equipment as instructed.

Give the garage a practical reset

Clear a path to the house, shutoffs, and equipment. Keep chemicals and liquids stored within their temperature and safety limits. Inspect the garage-door weather seal and operation, but leave springs and high-tension components to a qualified technician.

Never warm a vehicle inside a garage, even with the door open. Keep the garage-to-house separation intact, and do not use an outdoor heater in an enclosed space to protect stored items.

Finish by labeling unfamiliar equipment and keeping manuals together. A little preparation turns “What is this opening?” into a question you answer in daylight, well before a storm.

[Read this chapter online](#)

Chapter 19: What should I do before and during a winter power outage?

A winter outage affects more than the lights. Heating controls, blower motors, sump pumps, well equipment, medical devices, and communication systems may depend on electricity. Prepare for those dependencies instead of assuming that a gas supply alone keeps the house operating.

List the loads that matter

Identify what must operate to keep people safe and protect the building. Include medical needs and any refrigerated medications, then heating, critical water systems, and communication. Have a realistic plan for staying elsewhere when the home cannot remain safely occupied.

Keep charged power banks, flashlights, suitable batteries, necessary supplies, and contact information accessible. A connected home is less useful when the router and phone batteries are dead. Know which alerts depend on internet service and whether they have backup communication.

Situation: the gas furnace has fuel but no heat

A homeowner expects the furnace to run because the gas service still works. However, the controls and blower need electricity. The same kind of assumption can affect a boiler pump, a fireplace blower, or a sump pump.

Ask the service professional to explain your equipment's outage behavior before winter. If backup power is part of the plan, have the required loads and connection method designed for the actual equipment. Do not improvise a connection after the outage begins.

Use generators with a complete safety plan

CDC guidance calls for portable generators outdoors, at least 20 feet from doors, windows, and vents, with exhaust directed away from occupied buildings. Never operate one in a house, basement, garage, or enclosed porch. Maintain working CO alarms. See the [CDC generator safety fact sheet](#).

Use appropriate weather protection and connections as the manufacturer directs. Never backfeed the house through a receptacle. A connection to building wiring needs correctly installed transfer equipment and a qualified electrician. Stop and cool the generator before refueling, following its instructions.

Protect people before the pipes

Monitor indoor conditions and the needs of vulnerable occupants. If the house cannot remain safely warm, relocate rather than rely on unsafe heaters. Use flashlights instead of creating additional fire risk with candles in busy temporary living areas.

Keep exterior doors closed as practical, but do not block required ventilation or appliance air openings. Never use an oven or grill as space heat. Review the [CDC's winter-storm guidance](#) for personal safety considerations.

Plan the building response

If an extended outage threatens plumbing, contact the appropriate professional about your home's systems. Turning off a main valve does not drain every pipe or make all water-dependent systems safe. Fire sprinklers, boilers, and other equipment require special consideration.

After power returns, check heating operation, accessible plumbing, sump controls, alarms, and schedules. Look for leaks as the house warms. Record any failure that exposed a weakness so the next outage has a better plan.

[Read this chapter online](#)

Chapter 20: How do I prepare the house before winter travel or an extended vacancy?

Leaving for a long weekend and closing an unoccupied property for months are different tasks. The preparation depends on the building, its systems, how long you will be away, and who can respond. A thermostat setting and a locked door are not a complete vacancy plan.

Identify what still needs water and power

Fire sprinklers, hydronic heating, humidifiers, well systems, sump equipment, and other installations can complicate a blanket instruction to shut off utilities. Ask the relevant service professional before changing supply arrangements. A main water shutoff does not empty all plumbing or protect every appliance.

For an extended unheated vacancy, obtain a professional winterization plan. Draining domestic plumbing and treating appropriate fixtures requires a system-specific procedure. Do not pour automotive antifreeze into household plumbing or assume a partially drained system is safe.

Situation: the thermostat alert works, but nobody can get inside

A temperature monitor sends a warning while the homeowner is away. The designated neighbor has no key, does not know the alarm code, and cannot locate the main water valve. The warning is useful only if someone can act on it.

Choose a responsible local contact, confirm access, and provide a short instruction sheet. Include your service contacts, shutoff locations, equipment information, and what circumstances require an immediate emergency call rather than an attempted repair.

Arrange inspections with a purpose

Ask the person checking the home to verify heat, inspect known vulnerable plumbing, look at the basement, and report visible leaks or unusual conditions. A glance through the front window does not establish that the mechanical room is functioning.

Review your insurance policy's vacancy, inspection, and freeze-protection conditions. They may affect how often checks are required and what records you should keep. Get clarification from the insurer rather than relying on a generic online travel checklist.

Use sensors to support the plan

Leak and temperature sensors can add useful warning at selected locations. Consider under-sink areas, a mechanical room, a basement, or a historically cold addition. Confirm power, battery life, connectivity, alert recipients, and behavior when internet service fails.

An automatic water-shutoff system also needs to suit the building's water-dependent equipment. Have it specified and installed appropriately. Technology reduces some risks but does not eliminate the need for maintenance and response.

Complete the departure walkthrough

Confirm that hoses are disconnected, heat operates, vulnerable areas are accessible, and the sump discharge is clear. Set controls deliberately rather than leaving temporary holds or old schedules in place. Inspect appliance connections and close windows fully.

Leave contact instructions where the authorized person can find them, and check the forecast before departure. On return, inspect for signs of leakage and confirm normal operation before assuming an

uneventful trip means the house had no trouble. Travel preparation is strongest when observation, equipment, and a human response work together.

[Read this chapter online](#)

Chapter 21: How should I schedule and budget winterization work?

A useful schedule separates recurring maintenance from repairs and capital improvements. Replacing a worn door seal, diagnosing a wet basement corner, and rebuilding a poorly insulated addition are different kinds of work. Putting them on one undifferentiated list makes the season feel larger and less manageable than it needs to be.

Early fall: inspect and book the difficult work

Walk the exterior, locate drainage outlets, review roof concerns, and schedule heating or fireplace service as appropriate. Identify outdoor plumbing and equipment that need a winterization appointment. Obtain assessments for recurring leaks, freeze history, or major comfort problems.

If exterior repairs depend on temperature, dry weather, or curing conditions, allow room for those requirements. An autumn start date is not enough if the product cannot be installed in the conditions available when the crew arrives.

Before freezing weather: complete the essentials

Disconnect hoses, complete the correct outdoor water procedures, confirm heat operation, and test alarms. Address known pipe exposure, check access routes, and verify the sump and discharge according to equipment guidance. Put snow tools and approved traction materials where you can reach them.

Do not wait for a calendar milestone if freezing weather is forecast earlier. Follow the conditions and complete the highest-consequence items first.

During severe cold: observe the vulnerable locations

Check known cold rooms and plumbing areas, monitor heating behavior, and keep equipment vents clear where safely accessible. Use your planned controls rather than improvised heat sources. If a new problem appears, record the timing and conditions for the professional evaluating it.

After storms and thaws, inspect drainage routes, basement areas, and interior stains. A short follow-up can catch a change before it becomes a larger repair.

Situation: the budget will not cover everything this year

Suppose the list includes a recurring leak, several drafty windows, and a kitchen you want to refresh. Begin with diagnosis of the leak and any safety or freeze risk. Then compare targeted window repairs and broader envelope improvements. Schedule decorative work around the necessary construction instead of risking new finishes over an unresolved condition.

Ask for estimates that describe the scope, assumptions, access, materials, disposal, and finish restoration. A low price that excludes fixing the damaged substrate is not equivalent to a complete repair proposal.

Prioritize by consequences and evidence

Consider what happens if an item fails, how strong the evidence is, whether the repair unlocks another improvement, and whether waiting makes access more expensive. A hidden pipe repair may be economical while a bathroom is already open, even if it was not the original visual priority.

Keep a contingency for discoveries appropriate to the work and existing conditions. Do not treat a general percentage as proof that every unknown is covered. Ask how changes will be documented and approved.

End the season with a short record of completed work, unresolved conditions, photographs, and the next review date. That record makes next autumn's preparation faster and gives future remodeling decisions a reliable foundation.

[Read this chapter online](#)

Chapter 22: What are the winterization questions homeowners ask most often?

Should I replace all the windows to lower the heating bill?

Start with diagnosis. Windows can be part of the problem, but air leakage at ceilings, incomplete insulation, distribution problems, and equipment performance may also matter. Repair obvious operating defects and consider an energy assessment before choosing a large replacement project. Ask which measured conditions the proposal will improve and how the installation addresses water management.

Will extra attic insulation stop every draft?

No. Insulation and air sealing perform related but different jobs. A ceiling penetration can continue to leak air through or around insulation. Review the air barrier, moisture conditions, and roof assembly before adding material. Correct detailing around fixtures, access panels, and flues matters as much as broad coverage.

Does cleaning the gutters prevent ice dams?

It helps maintain drainage, but ice-dam risk also involves roof temperature and heat flow. A recurring problem needs assessment of the roof and the construction below it. Adding gutter heat cable or more vents without understanding the mechanism may leave the underlying defect unresolved. Use a coordinated diagnosis rather than a single-product promise.

Are foam faucet covers enough?

They can supplement protection where appropriate, but they do not replace disconnecting attachments or following the faucet's draining procedure. They also do not fix improper installation or an unheated valve location. Identify the faucet and its actual requirements, particularly if it has frozen before.

Should every faucet drip when temperatures fall?

A small flow can help protect certain vulnerable lines during severe cold, but it is not a universal household operating rule. The plumbing route, local utility guidance, water availability, and existing exposure matter. Discuss recurrent vulnerability with a plumber rather than relying on dripping as the long-term repair.

Can I turn off the water when I leave town?

It may be appropriate for some domestic plumbing arrangements, but get advice for the actual house. Fire sprinklers, boilers, and other water-dependent equipment can change the answer. Closing a valve also does not drain the system. Pair any shutdown decision with a plan for heat, inspections, and emergency response.

How often should I change the furnace filter?

Follow the equipment and filter instructions and inspect based on actual conditions. Different filters, pets, occupancy, and remodeling dust affect loading. Confirm the correct type and size with your service technician. Replacing a suitable filter with a much more restrictive one without checking compatibility can create a new airflow problem.

Is a cold bathroom solved by heated tile?

Floor warming can improve comfort, but diagnose drafts, insulation defects, distribution issues, and pipe exposure first. A comfortable surface does not demonstrate that the concealed floor cavity is protected. Plan the enclosure and plumbing, then choose the comfort feature as part of a complete installation.

Can I test my sump pump with a bucket of water?

Many systems allow a controlled water test, but use the instructions for the specific pump and basin. Confirm what kind of system you have, observe safe electrical boundaries, and do not disturb sealed covers. The important result is verified automatic operation and discharge, not the number of gallons added.

How do I know when to stop a DIY repair?

Stop when the condition is unsafe, the system is unfamiliar, access is hazardous, or the proposed repair would conceal an undiagnosed problem. Combustion work, electrical changes, concealed plumbing, significant moisture damage, and structural concerns often require qualified help. A useful DIY skill is knowing what to document for the right specialist.

What should I do with conflicting advice?

Identify whether the advice concerns the same material, equipment, and building assembly. A suggestion for a vented attic may be wrong for a conditioned roof. A thermostat routine for one heating system may not suit another. Use manufacturer instructions, local requirements, and a professional familiar with the home to resolve the difference.

What is the most valuable thing to finish today?

Choose the unresolved item with the greatest near-term consequence: an active leak, unsafe heat, a known freeze exposure, or blocked drainage. If none is present, complete a walkthrough and document what you find. Clear priorities are more useful than a long list of products purchased without a diagnosis.

[Read this chapter online](#)

Your final inside-and-out winter checklist

- Water outside: check roof runoff, downspouts, outlets, grading, wells, and stair drains.
- The enclosure: inspect roof concerns, exterior joints, door seals, attic access, insulation gaps, and cold-room exposures.
- Plumbing: disconnect hoses, winterize outdoor equipment correctly, assess vulnerable indoor routes, and identify shutoffs.
- Heat and air: service equipment as needed, inspect the correct filter, confirm controls, and check ventilation and moisture.
- Basement protection: verify sump operation and discharge, review backup equipment, and inspect after a thaw.
- Safety and access: test alarms, review heater and fireplace use, repair unsafe entries, and prepare lighting and snow equipment.

- People and response: plan for outages, travel checks, vulnerable occupants, and the person who can act on an alert.

Use this checklist to confirm actions, not to substitute for the explanations in the chapters. Mark anything uncertain for assessment and keep the record with your home maintenance information.

Build a home that performs behind the finishes

A well-prepared home is the result of many details working together. Roof water reaches a suitable outlet. Warm room air stays where it belongs. Plumbing follows a protected route. Ventilation removes moisture. The household knows what to do when a system needs attention.

Those same principles belong in a remodeling project. When a kitchen, bathroom, or basement is opened for improvement, it is an opportunity to address the hidden conditions that affect comfort and durability. The finished surfaces should be the final layer of a sound plan.

Trends Kitchen & Bathroom Specialists works with Kansas City-area homeowners to connect everyday needs with thoughtful design and careful construction. If your winter walkthrough reveals a remodeling need, bring the photographs, history, and priorities to the conversation. They are useful starting points for work designed to last.

We do it right the first time.

Sources and further reading

The links below support the technical guidance and provide equipment-specific or more detailed information. Reviewed for this October 2026 edition. Use current manufacturer instructions for the exact product in your home.

- [National Weather Service: Kansas City/Pleasant Hill forecasts and alerts](#)
- [ENERGY STAR: sealing and insulating your home](#)
- [ENERGY STAR: attic air sealing](#)
- [Building Science Corporation: ice-dam mechanisms and prevention](#)
- [American Red Cross: frozen-pipe prevention and response](#)
- [PRIER: frost-resistant faucet operation and freeze-damage causes](#)
- [U.S. Department of Energy: thermostat comfort and savings](#)
- [U.S. Department of Energy: heat-pump and dual-fuel thermostat controls](#)
- [U.S. Environmental Protection Agency: moisture and humidity](#)
- [ENERGY STAR: ventilation and indoor air quality](#)
- [Zoeller Pump Company: product support and system guidance](#)
- [U.S. Consumer Product Safety Commission: heating safety](#)
- [Centers for Disease Control and Prevention: generator safety](#)
- [Centers for Disease Control and Prevention: winter-storm safety](#)